


ISO 1479

Hexagon head tapping screws



Standard	ISO 1479		
Product Type	ISO 1479:2011 specifies the characteristics of hexagon head tapping screws with thread sizes from ST 2,2 to ST 9,5 inclusive.		
Material	Stainless Steel, Carbon Steel		
Surface Finish	Passivated, Plain, Zinc Plated, Dacromet		
Size Range	ST2.2 - ST9.5	Length Range	4.5-50 mm
Thread	Tapping screw thread (ST) per ISO 1478		

BASIS OF SPECIFICATION

WHICH STANDARD GOVERNS WHAT

Dimensions to	ISO 1479:2011
Carbon steel / Alloy steel mechanical properties to	ISO 2702:2022
Stainless steel mechanical properties to	ISO 3506-4:2025
Product grade	A

DIMENSIONAL DATA - SIZES WE SUPPLY

ALL DIMENSIONS PER THE STANDARD

d	P	a (max)	s (max)	s (min)	e (min)	k	k (min)	r (min)	y (ref)	y (ref)	y (ref)
Diameter - mm	Thread Pitch - mm	Thread Runout - mm	Width Across Flats - mm	Width Across Flats - mm	Width Across Corners - mm	Nominal Head Height - mm	Head Height - mm	Radius - mm	Point Length - C - mm	Point Length - F - mm	Point Length - R - mm
ST2.2	0.8	0.8	3.2	3.02	3.38	1.6	1.3	0.1	2	1.6	-
ST2.9	1.1	1.1	5	4.82	5.4	2.3	2	0.1	2.6	2.1	-
ST3.5	1.3	1.3	5.5	5.32	5.96	2.6	2.3	0.1	3.2	2.5	2.7
ST4.2	1.4	1.4	7	6.78	7.59	3	2.6	0.2	3.7	2.8	3.2
ST4.8	1.6	1.6	8	7.78	8.71	3.8	3.3	0.2	4.3	3.2	3.6
ST5.5	1.8	1.8	8	7.78	8.71	4.1	3.6	0.25	5	3.6	4.3
ST6.3	1.8	1.8	10	9.78	10.95	4.7	4.1	0.25	6	3.6	5
ST8	2.1	2.1	13	12.73	14.26	6	5.2	0.4	7.5	4.2	6.3
ST9.5	2.1	2.1	16	15.73	17.62	7.5	6.5	0.4	8	4.2	-

TECHNICAL SPECIFICATIONS

Surface Finish	Passivated, Plain, Zinc Plated, Dacromet
----------------	--

MARKING

Steel — No marking clause

What	None. Neither the product standard nor ISO 2702 contains a marking clause
Sizes	
Clause	ISO 2702:2011, Clauses 1 to 6 (Scope, Normative references, Materials, Requirements, Acceptance, Test methods), none of which is a marking clause

Stainless steel — Not mandatory on the part; required on the package

What	Marking the part is not mandatory. Where the hardness class symbol is marked, the manufacturer identification mark shall be there as well, as far as technically possible; the mark shall carry the steel group and hardness class, for example A4-20H. On the package, marking is required without exception: manufacturer and/or distributor identification, the steel group and hardness class symbol, and the manufacturing lot number to ISO 16426
Where	On the part where marked, and on the package in every case
Sizes	All sizes
Clause	ISO 3506-4:2009, 3.2.1 to 3.2.4, with 3.3 on delivery condition

Checked at both ends: the product standard runs only to Clause 5 Designation, and ISO 2702:2011 has no marking clause at all, so steel tapping screws to this standard carry no marking obligation.

Confirm the ordered property class before production.

INSPECTION DOCUMENTS WE CAN ISSUE

EN 10204 3.1 material certificate	Can be included when agreed in the order.
Dimensional inspection report	Can be provided for the agreed inspection scope.
Certificate of conformity	Can be issued against the confirmed order requirements.
Mechanical test report	Available when the required tests are agreed before production.
Chemical analysis report	Available when the material verification scope is agreed.
Coating inspection report	Can record the coating checks agreed for the order.

REFERENCES & NOTES

Note: Dimensional values follow the selected execution standard. Material properties and batch test results are included only when declared or supported by the applicable certificate or test report.